

RS286HNX01D01-BK

Key Features

- ✧ High brightness 1500nits
- ✧ Protection level IP 65
- ✧ LED Backlight
- ✧ Wide Viewing Angle of 178°(H), 178°(V)
- ✧ Operation Temperature (-20˚C~60˚C)
- ✧ LCD Blacking Defect Free
- ✧ Low Power Consumption
- ✧ BL MTBF: 50,000 hours



Specifications

Model Name	RS286HNX01D01-BK
Screen Size	28.6″
Display Area (mm)	698.4(H) x 196.43(V)
Brightness	1500 cd/m^2
Resolution	1920x540
Aspect Ratio	32 : 9
Contrast Ratio	4000 : 1
Response Time (Typical)	8 (Typ.)(G to G) (ms)
Viewing Angle	89/89/89/89 (Min.)(CR≥10)
Display Colors	16.7M
OS	N/A
CPU	N/A
RAM	N/A
HDD	N/A
Glass	5mm glass
Touch Type (option)	EETI/ Projected Capacitive Touch (option)
Input Power	AC100-240V
Power Consumption	50W
Input Interface	PC AUDIO IN*1 EARPHONE OUT*1 DVI*1 VGA*1 HDMI *1 AC IN*1
Dimensions (mm)	756.5 x 254.5 x 73mm
Mounting	400*200
Weight (Net)	14.5
IP (Ingress Protection)	IP65
Operating Temperature	-20℃ ~ 60℃
Storage Temperature	-20℃ ~ 60℃

The information described in this specification is preliminary and can be changed without prior notice.





Mechanical Drawing

Unit:mm

