55" Full Outdoor Monitor

Key Features

- LED Backlight
- Sunlight Readable
- High brightness2000nits
- BL MTBF: 50,000 hours
- Low Power Consumption
- LCD Blacking Defect Free
- Wide Viewing Angle of 178°(H), 178°(V)
- Wide Operation Temperature (-20 °C~70°C)
- The light sensor automatically adjusts the brightness



Specifications

Model Name	RS550HNX02-N		
Screen Size	55"		
Display Area (mm)	1209.6(H)×680.4(V) mm		
Dimensions (mm)	1280.6(H)×751.4(V)×98.5(D) mm		
Brightness	2000 cd/m^2		
Resolution	1920 × 1080		
Aspect Ratio	16 : 9		
Contrast Ratio	1300 : 1		
Response Time (Typical)	6(Typ.)(Tr/Td) (ms)		
Viewing Angle	89/89/89/89 (Min.)(CR≥10)		
Display Colors	16.7M		
Glass	Tempered Glass, AR or AG (optional), OCR optical bonding		
Touch Type	PCAP		
Input Power	AC 100~240V		
Power Consumption	150W(.typ)		
Radiator System	Passive heat dissipation without fan		
Mounting	400x600mm 4-M8		
Weight (Net)	TBD		
IP（Ingress Protection）	IP66		
Operating Temperature	-20 °C~70 °C		
Storage Temperature	-25 °C~80 °C		
OS	Android	windows	Monitor
Input Interface	AC IN	AC IN	AC IN
	HDMI*1 RJ45*1 USB*2 (optional ,4 pcs max)	HDMI*2 RJ45*2 USB*2 (optional ,4 pcs max)	HDMI*1

The information described in this specification is preliminary and can be changed without prior notice.

Outline Dimensions

Mechanical Drawing **Unit: mm**



