# 65" Window Facing Display with local dimming

## Key Features

- LED Backlight
- Sunlight Readable
- High brightness2500nits
- BL MTBF: 50,000 hours
- Low Power Consumption
- LCD Blacking Defect Free
- LED Backlight with local dimming
- Wide Viewing Angle of 178°(H), 178°(V)
- Wide Operation Temperature (-20 °C~70°C)
-




## Specifications

| Model Name | RS650DNX01 | | |
|---|---|---|---|
| Screen Size | 65" | | |
| Display Area (mm) | 1428.48(H)×803.52(V) mm | | |
| Dimensions (mm) | 1473.4(H)×846.5(V)×96.3(D) mm | | |
| Brightness | 4000 cd/m$^2$ | | |
| Resolution | 3840 x 2160 | | |
| Aspect Ratio | 16 : 9 | | |
| Contrast Ratio | 1500 : 1 | | |
| Response Time (Typical) | 8(Typ.)(Tr/Td) (ms) | | |
| Viewing Angle | 89/89/89/89 (Min.)(CR≥10) | | |
| Display Colors | 16.7M | | |
| Glass | N/A | | |
| Touch Type | N/A | | |
| Input Power | AC 100-240 V | | |
| Power Consumption | 500W(.typ) | | |
| Radiator System | The fan will automatically start to cool down when the temperature exceeds 35℃ | | |
| Mounting | 400x400 mm 4-M8 | | |
| Weight (Net) | 45 kg | | |
| Operating Temperature | -20 ℃~70 ℃ | | |
| Storage Temperature | -25 ℃~80 ℃ | | |
| OS | Android | windows | Monitor |
| Input Interface | AC IN<br>USB*2<br>HDMI*1<br>RJ45*1<br>EARPHONE OUT*1<br>TF*1 | AC IN<br>HDMI*2<br>RS232*1<br>USB*2<br>RJ45*2 | AC IN<br>HDMI*2<br>USB*1<br>AC IN*1 |

**The information described in this specification is preliminary and can be changed without prior notice.**

# Outline Dimensions

**Mechanical Drawing** **Unit: mm**

