32" Full Outdoor Monitor

Key Features

- LED Backlight
- Sunlight Readable
- High brightness2000nits
- BL MTBF: 50,000 hours
- Low Power Consumption
- Protection level Ip66 Front
- LCD Blacking Defect Free
- Wide Viewing Angle of 178°(H), 178°(V)
- Wide Operation Temperature (-20 °C~70°C)
- The light sensor automatically adjusts the brightness



Specifications

Model Name	RS320HNX01-N		
Screen Size	32"		
Display Area (mm)	698.4(H)×392.85(V) mm		
Dimensions (mm)	770.5(H)×465.5(V)×90.5(D) mm		
Brightness	2000 cd/m^2		
Resolution	1920 × 1080		
Aspect Ratio	16 : 9		
Contrast Ratio	1300 : 1		
Response Time (Typical)	6(Typ.)(Tr/Td) (ms)		
Viewing Angle	89/89/89/89 (Min.)(CR≥10)		
Display Colors	16.7M		
Glass	Tempered Glass, AR or AG (optional), OCR optical bonding		
Touch Type	CTP		
Input Power	AC 100~240V		
Power Consumption	130W(.typ)		
Radiator System	Passive heat dissipation without fan		
Mounting	400x200mm 4-M8		
Weight (Net)	28.5kg		
IP（Ingress Protection）	IP66		
Operating Temperature	-20 ℃~70 ℃		
Storage Temperature	-25 ℃~ 80 ℃		
OS	Android	windows	Monitor
Input Interface	AC IN HDMI*1 RJ45*1 USB*2 (optional ,3 pcs max)	AC IN HDMI*2 RJ45*2 USB*2 (optional ,3 pcs max)	AC IN HDMI*1

The information described in this specification is preliminary and can be changed without prior notice.

Outline Dimensions

Mechanical Drawing **Unit: mm**

