55" Full Outdoor Digital Signage

Key Features

- High brightness 3500nits
- LED Backlight
- Sunlight Readable
- The light sensor automatically adjusts the brightness
- LCD Blacking Defect Free
- Low Power Consumption
- BL MTBF: 50,000 hours
- Wide Operation Temperature (-20 °C~70°C)



Specifications

Model Name	RS550HNX03-P04-BK
Screen Size	55"
Display Area (mm)	1209.6(H)×680.4(V) mm
Brightness	3500 cd/m^2
Resolution	3840 x 2160
Aspect Ratio	16 : 9
Contrast Ratio	1100 : 1
Response Time (Typical)	8(Typ.)(Tr/Td) (ms)
Viewing Angle	89/89/89/89 (Min.)(CR≥10)
Display Colors	16.7M
OS	Windows 10
Glass	5MM Glass,Front AR IK 10
Touch Type	PCAP
Input Power	AC 100~240V
Power Consumption	<260W
Radiator System	The fan will automatically start to cool down when the temperature exceeds 35℃
Input Interface	RJ45*1 USB*2 AC*1
Dimensions (mm)	1279.5*750.5*98.5 mm
Mounting	400x400mm 4-M8,MAX DEPTH=8mm
Weight (Net)	66kg
IP（Ingress Protection）	IP66
Operating Temperature	-20 ℃~70 ℃
Storage Temperature	-20 ℃~ 60 ℃

The information described in this specification is preliminary and can be changed without prior notic.

Outline Dimensions

Mechanical Drawing **Unit: mm**



