75" Full Outdoor Digital Signage

Key Features

- High brightness 4000nits
- LED Backlight
- Sunlight Readable
- The light sensor automatically adjusts the brightness
- LCD Blacking Defect Free
- Low Power Consumption
- BL MTBF: 50,000 hours
- Wide Operation Temperature (-20 °C~70°C)



Specifications

Model Name	**RS750HNX05-P01-BK**
Screen Size	75"
Display Area (mm)	1649.66(H)×927.94(V) mm
Brightness	4000 cd/m^2
Resolution	3840 x 2160
Aspect Ratio	16 : 9
Contrast Ratio	1200 : 1
Response Time (Typical)	8(Typ.)(Tr/Td) (ms)
Viewing Angle	89/89/89/89 (Min.)(CR≥10)
Display Colors	1.07B
OS	Windows 11
Glass	5mm+4mm Glass,Front AR IK 10
Touch Type	N/A
Input Power	AC 100~240V
Power Consumption	800W(.typ)
Radiator System	The fan will automatically start to cool down when the temperature exceeds 35℃
Input Interface	RJ45*1 USB*2 AC*1 Audio*1
Dimensions (mm)	1730.7*1009*107 mm
Mounting	600x800mm 4-M8,MAX DEPTH=8mm
Weight (Net)	135kg
IP（Ingress Protection）	IP66
Operating Temperature	-20 ℃~70 ℃
Storage Temperature	-20 ℃~ 60 ℃

The information described in this specification is preliminary and can be changed without prior notic.

Outline Dimensions

Mechanical Drawing **Unit: mm**



