# 21.5" Full Outdoor Monitor

## Key Features

- LED Backlight
- Sunlight Readable
- High brightness1000nits
- BL MTBF: 50,000 hours
- Low Power Consumption
- Protection level Ip66 Front
- LCD Blacking Defect Free
- Wide Viewing Angle of 178°(H), 178°(V)
- Wide Operation Temperature (-20 °C~70°C)
- The light sensor automatically adjusts the brightness




## Specifications

| Model Name | RS215HNX01-N | | |
|---|---|---|---|
| Screen Size | 21.5" | | |
| Display Area (mm) | 478.656(H)×260.28(V) mm | | |
| Dimensions (mm) | 526.5(H)×318(V)×62(D) mm | | |
| Brightness | 1000 cd/m$^2$ | | |
| Resolution | 1920 × 1080 | | |
| Aspect Ratio | 16 : 9 | | |
| Contrast Ratio | 3000 : 1 | | |
| Response Time (Typical) | 20(Typ.)(Tr/Td) (ms) | | |
| Viewing Angle | 89/89/89/89 (Min.)(CR≥10) | | |
| Display Colors | 16.7M | | |
| Glass | Tempered Glass, AR or AG (optional), OCR optical bonding | | |
| Touch Type | N/A | | |
| Input Power | AC 100~240V | | |
| Power Consumption | TBD | | |
| Radiator System | Passive heat dissipation without fan | | |
| Mounting | 100x100mm 4-M4 | | |
| Weight (Net) | TBD | | |
| IP（Ingress Protection） | IP66 | | |
| Operating Temperature | -20 ℃~70 ℃ | | |
| Storage Temperature | -25 ℃~ 80 ℃ | | |
| OS | Android | windows | Monitor |
| Input Interface | AC IN | AC IN | AC IN |
| | HDMI*1<br>RJ45*1<br>USB*2<br>(optional ,2 pcs max) | HDMI*2<br>RJ45*2<br>USB*2<br>(optional ,2 pcs max) | HDMI*1 |

**The information described in this specification is preliminary and can be changed without prior notice.**

# Outline Dimensions

**Mechanical Drawing** **Unit: mm**







